



命名规则	B	-	M3	-	2	-	ZU		
	B	-	S	-	M3	-	2	-	X
	↓	↓	↓	↓	↓	↓	↓	↓	↓
	产品	材料	螺纹	尾缀	表面处				
	类型	代码	代码	代码	理类型				

所有尺寸：毫米

公制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码	A Max.	最小板厚 (1)	板开口尺寸 +0.08	B Max.	C Max.	E ± 0.25	F Min.	L Max.	T ± 0.25	孔中心到板边缘的最小距离 (2)
		螺母材料													
		碳钢	不锈钢												
M3x0.5	B	BS	M3	1	0.97	1.0	4.22	3.84	4.2	6.35	5.3	8.5	9.6	4.8	
				2	1.38	1.4									
M4x0.7	B	BS	M4	1	0.97	1.0	5.41	5.2	5.38	7.95	7.1	9.8	11.2	6.9	
				2	1.38	1.4									
M5x0.8	B	BS	M5	1	0.97	1.0	6.35	6.02	6.33	8.75	7.1	9.8	11.2	7.1	
				2	1.38	1.4									
M6x1.0	B	BS	M6	1	1.38	1.4	8.75	7.8	8.73	11.1	7.8	12.7	14.3	8.6	
				2	2.21	2.29									

所有尺寸：英寸

英制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码	A Max.	最小板厚 (1)	板开口尺寸 +.003/- .000	B Max.	C Max.	E ± .010	F Min.	L Max.	T ± .010	孔中心到板边缘的最小距离 (2)
		螺母材料													
		碳钢	不锈钢												
.112-40 (#4-40)	B	BS	440	1	.038	.040	.166	.150	.165	.250	.210	.335	.380	.19	
				2	.054	.056									
.138-32 (#6-32)	B	BS	632	1	.038	.040	.1875	.169	.187	.280	.230	.335	.380	.22	
				2	.054	.056									
.164-32 (#8-32)	B	BS	832	1	.038	.040	.213	.204	.212	.310	.280	.385	.440	.27	
				2	.054	.056									
.190-32 (#10-32)	B	BS	032	1	.038	.040	.250	.235	.249	.340	.280	.385	.440	.28	
				2	.054	.056									
.250-20 (1/4-20)	B	BS	0420	1	.054	.056	.344	.305	.343	.430	.310	.500	.560	.34	
				2	.087	.090									

(1) 为了达到最好的性能，我们建议你根据实际板厚选择对应的螺母

(2) 为了最大限度的减少安装的板的变形，以及获得最好的性能，建议螺母安装需要和边缘保持足够的距离