



所有尺寸：毫米

公制螺纹	螺纹规格	型号	螺纹代码	尾缀码	A Max.	最小板厚	开口尺寸 +0.08/ -0.0	C Max.	E ± 0.25	T ± 0.25	孔中心 到板边缘 最小距离
	M3x0.5	SL	M3	1	0.98	1.0	4.22	4.2	6.35	1.5	4.8
			2	1.38	1.4						
M3.5x0.6	SL	M3.5	1	0.98	1.0	4.75	4.73	7.1	1.5	5.6	
			2	1.38	1.4						
M4x0.7	SL	M4	1	0.98	1.0	5.41	5.38	7.95	2.0	6.9	
			2	1.38	1.4						
M5x0.8	SL	M5	1	0.98	1.0	6.35	6.33	8.75	2.0	7.1	
			2	1.38	1.4						
M6x1.0	SL	M6	1	1.38	1.4	8.75	8.73	11.1	4.08	8.6	
			2	2.21	2.3						
M8x1.25	SL	M8	1	1.38	1.4	10.5	10.47	12.65	5.47	9.7	
			2	2.21	2.3						

所有尺寸：英寸

英制螺纹	螺纹规格	型号	螺纹代码	尾缀码	A Max.	最小板厚	开口尺寸 +.003/ -.000	C Max.	E ± .010	T ± .010	孔中心 到板边缘 最小距离
	.112-40 (#4-40)	SL	440	1	.038	.040	.166	.165	.250	.070	.19
2				.054	.056						
.138-32 (#6-32)	SL	632	1	.038	.040	.1875	.187	.280	.070	.22	
			2	.054	.056						
.164-32 (#8-32)	SL	832	1	.038	.040	.213	.212	.310	.090	.27	
			2	.054	.056						
.190-32 (#10-32)	SL	032	1	.038	.040	.250	.249	.340	.090	.28	
			2	.054	.056						
.250-20 (1/4-20)	SL	0420	1	.054	.056	.344	.343	.440	.170	.34	
			2	.087	.091						
.313-18 (5/16-18)	SL	0518	1	.054	.056	.413	.412	.500	.230	.38	
			2	.087	.091						