



所有尺寸：毫米

螺纹规格	型号规格			螺纹代码	头部形状	杆部形状	通盲孔	铆接厚度 e	安装孔 Do +0.15/ +0.05	杆径 D -0.03/ -0.10	头径 dk +/-0.5	头厚 K	总长 L Max	铆后长度 (参考) h Ref.
	螺母材料													
	碳钢	不锈钢	铝合金											
M3x0.5	CM CMK	CMS CMKS	CMA CMKA	M3	沉头	光杆 直纹	通孔	1.7-2.5	5.0	5.0	8.0	1.5	9.3	5.8
								2.5-3.5					10.3	
								3.5-4.5					11.3	
M4x0.7	CM CMK	CMS CMKS	CMA CMKA	M4	沉头	光杆 直纹	通孔	1.7-2.5	6.0	6.0	9.0	1.5	10.8	7.5
								2.5-3.5					11.8	
								3.5-4.5					12.8	
M5x0.8	CM CMK	CMS CMKS	CMA CMKA	M5	沉头	光杆 直纹	通孔	1.7-2.5	7.0	7.0	10.0	1.5	12.8	9.3
								2.5-3.5					13.8	
								3.5-4.5					14.8	
M6x1.0	CM CMK	CMS CMKS	CMA CMKA	M6	沉头	光杆 直纹	通孔	1.7-3.0	9.0	9.0	12.0	1.5	15.3	11.0
								3.0-4.5					16.8	
								4.5-6.0					18.3	
M8x1.25	CM CMK	CMS CMKS	CMA CMKA	M8	沉头	光杆 直纹	通孔	1.7-3.0	11.0	11.0	14.0	1.5	16.8	12.3
								3.0-4.5					18.3	
								4.5-6.0					19.8	
M10x1.5	CM CMK	CMS CMKS	CMA CMKA	M10	沉头	光杆 直纹	通孔	1.7-3.0	13.0	13.0	16.0	1.5	19.8	15.0
								3.0-4.5					21.3	
								4.5-6.0					22.8	

公制螺纹